

# MATERIAL SAFETY DATA SHEET

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Echelon Accent Color Primer  
 Product Code Identification Number: 78303406, 78303402, 78303408  
 GENERAL USE: Protective Coating  
 PRODUCT DESCRIPTION: Acrylic latex coating, slight ammonia odor



MANUFACTURER'S NAME H&K Paint Company	DATE PREPARED: July 21, 2007 SUPERSEDES: New	Page 1 of 4
ADDRESS (NUMBER, STREET, P.O. BOX) 21901 South Central Avenue (CITY, STATE AND ZIP CODE) Matteson, IL 60443-2801	TELEPHONE NUMBER FOR INFORMATION (888) 451-5463 EMERGENCY TELEPHONE NUMBER Infotrac (800) 535-5053 Outside USA (352) 323-3500	
DISTRIBUTOR'S NAME Same		
ADDRESS (NUMBER, STREET, P.O. BOX) (CITY, STATE AND ZIP CODE) COUNTRY USA	TELEPHONE NUMBER FOR INFORMATION EMERGENCY TELEPHONE NUMBER	

## SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS #	%	OSHA PEL		ACGIH TWA		SARA TITLE III	RQ LBS
			PPM	MG/M3	PPM	MG/M3		
2,2,4-trimethyl-1-1,3-pentanediol mono(2-methylpropanoate)	25265-77-4	1 - 5	not established					
Ethylene glycol (a,b,c)	107-21-1	1 - 5			39.4 C	127 C	Yes	5000
Stoddard solvent (Petroleum distillate, aliphatic)	8052-41-3	1 - 5	100	525	100	525		

(a,c) See Section 15

(b) A "C" in the OSHA PEL or ACGIH TWA column indicates ceiling limits, the concentration that should not be exceeded during any part of the working exposure.

## SECTION 3 - HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

WARNING! Harmful or fatal if swallowed, harmful if inhaled or absorbed through the skin. May cause allergic skin reaction. May cause irritation to skin, eyes, and respiratory tract. Affects central nervous system Hazard symbols for this product - Not classified. Risk Phrases - Not classified

### POTENTIAL HEALTH EFFECTS

**INHALATION:** High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

**SKIN:** Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.

**EYES:** High vapor concentration or contact may cause irritation and discomfort.

**INGESTION:** May result in vomiting; aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death. Large doses may be fatal.

**CARCINOGENICITY** NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No  
 This product contains trace amounts of the following substances known to the state of California to cause cancer: 1,4 Dioxane, Ethylene Oxide, and Acetaldehyde.

**MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: Echelon Accent Color Primer  
July 21, 2007

Page 2 of 4

**SECTION 4 - FIRST AID MEASURES**

**INHALATION:** Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

**SKIN:** Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

**EYES:** Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

**INGESTION:** DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

**SECTION 5 - FIRE FIGHTING MEASURES**

FLASH POINT (METHOD USED) Non-flammable	FLAMMABLE LIMITS	LEL: Not applicable	UEL: Not applicable
	AUTOIGNITION TEMPERATURE:	Not determined	NFPA CLASS: <b>None</b>

**GENERAL HAZARDS:** Product is not considered flammable or combustible. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.

**EXTINGUISHING MEDIA**  
Carbon dioxide, water, water fog, dry chemical, chemical foam

**FIRE FIGHTING PROCEDURES**  
Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**  
None

**HAZARDOUS COMBUSTION PRODUCTS**  
Smoke, fumes or vapors, oxides of carbon.

**SECTION 6 - ENVIRONMENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Small spills - wash to sanitary sewer with plenty of water.. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to SARA Title III, Section 313 40 CFR 372, and CERCLA 40 CFR 302 for complete regulations concerning reporting requirements.

**SECTION 7 - HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**ENGINEERING CONTR0LS**

The use of local exhaust ventilation is recommended. No other special controls are indicated.

**PERSONAL PROTECTION:**

**RESPIRATORY PROTECTION (SPECIFY TYPE):** None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

**PROTECTIVE GLOVES:** Neoprene, butyl or nitrile rubber gloves with cuffs.

**EYE PROTECTION:** Chemical safety goggles.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Safety eyewash station nearby.

**WORK / HYGIENIC PRACTICES:** Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

**MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: Echelon Accent Color Primer  
July 21, 2007

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20° C	VAPOR DENSITY (AIR = 1) > 1
SPECIFIC GRAVITY (WATER = 1) 1.192	EVAPORATION RATE (WATER = 1) < 1
SOLUBILITY IN WATER Dispersible	FREEZING POINT 32° F (0° C)
pH 8.5 - 9.5	APPEARANCE AND ODOR White viscous liquid, slight ammonia odor
BOILING POINT 176°F (80° C)	PHYSICAL STATE Liquid
VISCOSITY (KREBS) 103 - 108	

**SECTION 10 - STABILITY AND REACTIVITY**

STABILITY UNSTABLE: STABLE: X	CONDITIONS TO AVOID: Extreme temperatures, keep from freezing
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.	
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X	CONDITIONS TO AVOID: None

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Hazardous Ingredients	CAS #	EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
2,2,4-trimethyl-1-1,3-pentanediol mono(2-methylpropanoate)	25265-77-4	246-771-9	6860 mg / kg Oral - rat	Not established
Ethylene glycol (a,b,c)	107-21-1	203-473-3	4700 mg / kg Oral - rat	10876 mg / kg Inhalation - rat
Stoddard solvent (Petroleum distillate, aliphatic)	8052-41-3	232-489-3	> 5000 mg / kg Oral - rat	> 5500 mg / m3 / 4H Inhalation - rat
(a,c) See Section 15				

**SECTION 12 - ECOLOGICAL INFORMATION**

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Product is classified as non-hazardous, however, non-hazardous materials may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

**SECTION 14 - TRANSPORT INFORMATION**

PROPER SHIPPING NAME: Non - Hazardous for Transport

DOT HAZARD CLASS / Pack Group: Not regulated  
REFERENCE: Not Applicable  
UN / NA IDENTIFICATION NUMBER: None  
LABEL: None Required  
HAZARD SYMBOLS: None

IATA HAZARD CLASS / Pack Group: Not regulated  
IMDG HAZARD CLASS: Not regulated  
RID/ADR Dangerous Goods Code: Not regulated  
UN TDG Class / Pack Group: Not regulated  
Hazard Identification Number (HIN): None

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

**MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: Echelon Accent Color Primer  
 July 21, 2007

**SECTION 15 - REGULATORY INFORMATION**

**TSCA (Toxic Substance Control Act)**

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

**SARA TITLE III (Superfund Amendments and Reauthorization Act)**

311/312 Hazard Categories  
 Immediate health

313 Reportable Ingredients:

(a) Indicates a toxic chemical subject to annual reporting requirements of Section 313 of SARA Title III of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

**CERCLA (Comprehensive Response Compensation and Liability Act)**

(c) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24000 lbs) or greater amounts, according to 40 CFR 302.

**California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986**

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

**CPR (Canadian Controlled Products Regulations)**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: Not controlled

**IDL (Canadian Ingredient Disclosure List)**

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.

**DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)**

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

**EINECS (European Inventory of Existing Commercial Chemical Substances)**

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

**EC Risk Phrases**

Not classified

**SYMBOL(S) REQUIRED FOR LABEL**

None

**EC Safety Phrases**

S2 Keep out of the reach of children.  
 S24/25 Avoid contact with skin and eyes

**SECTION 16 - OTHER INFORMATION**

No specific notes.

**HMIS HAZARD RATINGS**

HEALTH	1	* = Chronic Health Hazard	2 = MODERATE
FLAMMABILITY	0	0 = INSIGNIFICANT	3 = HIGH
PHYSICAL HAZARD	0	1 = SLIGHT	4 = EXTREME

**REVISION SUMMARY:**

This MSDS has been revised in the following sections:  
 No changes noted

MSDS Prepared by: Comprehensive Data Base, Inc.  
 P.O. Box 395  
 Intercession City, FL 33848 USA  
 (863) 644 - 3298 www.compdatabase.com or www.msds.cc

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.