

# echelon™

## Color Transforming Latex Ceiling Paint 7631129

### Features

- Goes on blue-dries to clean pure white in hours
- Interior use Only
- Soap and Water Clean-Up

### Where to Use

An excellent matte white latex finish for interior ceilings. This heavy bodied product is specially formulated to minimize drips and spatters for overhead application. Dries quickly to a flat finish that reduces reflection and glare.

### Surface Preparation

Wash previously painted surfaces to remove dirt, grease, oil, mildew, wax and other contaminants. Thoroughly rinse the washed areas and allow to dry completely.

Patch cracks and surface imperfections. Sand repaired areas smooth. Wipe off all sanding dust with a damp cloth. Spot prime patched areas with the appropriate primer or undercoater.

Existing finishes that are porous or that have deteriorated may require an undercoater to seal the surface. After cleaning, porous ceilings should be primed with Echelon Multi-Purpose Primer.

### Thinning & Clean Up

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean up.

### Limitations

Do not apply when air surface or product temperature is below 50° F (10°C) or if temperature might drop to this level within 4 hours of application.

Do not apply in temperatures above 90°F (32°C).

Keep from freezing.

### Equipment

Conv. Spray:	Use Sprayer Manufacturers Recommendations
Airless Spray:	Use Sprayer Manufacturers Recommendations
Brush:	Quality nylon / polyester brush
Roller:	3/8" Nap Cover
Pad:	Standard

### Packaging

Gallons  
1 oz blue tint additive

### Colors

Ceiling white (Do Not Tint)

### Specification Data

<b>Type:</b>	Acrylic Latex
<b>Finish:</b>	Flat
» Gloss:	3 Max @ 60°
<b>% Solids :</b>	
» By Weight:	55%
» By Volume:	33%
<b>Wt./Gallon:</b>	12.33 lbs.± 0.1
<b>Flashpoint:</b>	N/A
<b>VOC lbs./gal (max):</b>	0.83
<b>VOC grm/ltr (max):</b>	100
<b>Thinner:</b>	Water
<b>Clean up:</b>	Soap and Water
<b>Dry Time:</b>	
» To Touch:	½ hour
» To Recoat:	2 - 4 hours
» To Service:	Overnight
<b>Thickness:</b>	
» Dry:	1.3 mil
» Wet:	4.0 mil
<b>Coverage:</b>	400 sq. ft./gal (on smooth surfaces)
<b>Flame Spread Rate:</b>	Class A (0-25 on non-combustible surfaces)