

# echelon™

## Interior Latex Flat 7631 Series

### Features

- Interior Use Only
- 12 Year Durability
- Low Spatter
- Good Adhesion
- Washable
- Soap and Water Clean-up

### Where to Use

Ideal for interior walls of dining rooms, bedrooms and formal living areas. Use on properly prepared plaster, drywall, wood, masonry, plywood and properly primed metal. For maximum scrubability on woodwork, cabinets and hard use rooms such as bathrooms and kitchens, we recommend Echelon Semi-Gloss.

### Surface Preparation

Wash previously painted surfaces to remove dirt, grease, oil, mildew, wax and other contaminants. Thoroughly rinse the washed areas and allow to dry completely.

Patch cracks and surface imperfections. Sand repaired areas smooth. When applying over satin, semi-gloss or gloss finishes, sand lightly with medium grit sandpaper for maximum adhesion. Wipe off all sanding dust with a damp cloth. Spot prime patched areas with the appropriate primer or undercoater. Prime unpainted drywall, masonry, and unpainted plaster or wood with Echelon Multi-Purpose Primer. It is essential that plaster be completely dry before priming; allow a minimum of 30 days for new plaster to cure before using Echelon Multi-Purpose Primer.

Prime bare metal with an appropriate metal primer.

### Thinning & Clean Up

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean up.

### Limitations

Do not apply when air surface or product temperature is below 50° F (10°C) or if temperature might drop to this level within 4 hours of application.

Do not apply in temperatures above 90°F (32°C).

Keep from freezing.

### Equipment

Conv. Spray:	Use Sprayer Manufacturers Recommendations
Airless Spray:	Use Sprayer Manufacturers Recommendations
Brush:	Quality nylon / polyester brush
Roller:	3/8" Nap Cover
Pad:	Standard

### Packaging

Gallons, Quarts

### Colors

White & Tint Bases

### Specification Data

<b>Type:</b>	Acrylic Latex
<b>Finish:</b>	Flat
Gloss:	<5 @ 60°
Sheen:	<5 @ 85°
<b>% Solids:</b>	
By Weight:	47%
By Volume:	32%
<b>Wt./Gallon:</b>	10.80 ± .10
<b>Flashpoint:</b>	N/A
<b>VOC lbs./gal (max):</b>	0.83
<b>VOC grm/ltr (max):</b>	100
<b>Thinner:</b>	Water
<b>Clean up:</b>	Soap and Water
<b>Dry Time:</b>	
To Touch:	½ hour
To Recoat:	2 - 4 hours
To Service:	Overnight
<b>Thickness:</b>	
Dry:	1.3 mil
Wet:	4.0 mil
<b>Coverage:</b>	400 sq. ft./gal (on smooth surfaces)
<b>Flame Spread Rate:</b>	Class A (0-25 on non-combustible surfaces)