

echelon™

Interior Latex Semi-Gloss 7634 Series

Features

- Interior Use Only
- 12 Year Durability
- Good Scrubbability
- Low Spatter
- Good Adhesion
- Washable
- Non-Yellowing
- Soap and Water Clean Up

Where to Use

For properly prepared interior walls of plaster, wallboard and masonry. Ideally suited for living room, halls, family room, dining room, bedroom, children's rooms, and any hard use area. Can also be used over properly primed metal or wood.

Surface Preparation

Wash previously painted surfaces to remove dirt, grease, oil, mildew, wax and other contaminants. Thoroughly rinse the washed areas and allow to dry completely.

Patch cracks and surface imperfections. Sand repaired areas smooth. When applying over satin, semi-gloss or gloss finishes, sand lightly with medium grit sandpaper for maximum adhesion. Wipe off all sanding dust with a damp cloth. Spot prime patched areas with the appropriate primer or undercoater. Prime unpainted drywall, masonry, and unpainted plaster or wood with Echelon Multi-Purpose Primer. It is essential that plaster be completely dry before priming; allow a minimum of 30 days for new plaster to cure before using Echelon Multi-Purpose Primer.

Prime bare metal with an appropriate metal primer.

Thinning & Clean Up

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean up.

Limitations

Do not apply when air surface or product temperature is below 50° F (10°C) or if temperature might drop to this level within 4 hours of application.

Do not apply in temperatures above 90°F (32°C).

Keep from freezing.

Equipment

Conv. Spray:	Use Sprayer Manufacturers Recommendations
Airless Spray:	Use Sprayer Manufacturers Recommendations
Brush:	Quality nylon / polyester brush
Roller:	3/8" Nap Cover
Pad:	Standard

Packaging

Gallons, Quarts

Colors

White & Tint Bases

Specification Data

Type:	Acrylic Latex
Finish:	Semi-Gloss
Gloss:	45 - 50 @ 60°

% Solids:

By Weight:	44%
By Volume:	29%

Wt./Gallon: 10.53 ± .10

Flashpoint: N/A

VOC lbs./gal (max): 1.25

VOC grm/ltr (max): 150

Thinner: Water

Clean up: Soap and Water

Dry Time:

To Touch:	½ hour
To Recoat:	2 - 4 hours
To Service:	Overnight

Thickness:

Dry:	1.2 mil
Wet:	4.0 mil

Coverage: 400 sq. ft./gal

(on smooth surfaces)

Flame Spread Rate:

Class A
(0-25 on non-combustible surfaces)