

echelon™ Premier

Interior Latex Satin

7613 Series

Features

- Exceptional Washability
- Superior Coverage
- Precise Color Technology
- Lifetime Warranty
- Featuring Scotchgard™ Protection

Where to Use

Ideal for any room in the house including kitchens, bathrooms, hallways, and other hard-use areas. Use on properly prepared plaster, drywall, wood, masonry, plywood, and properly primed metal.

Surface Preparation

Wash previously painted surfaces to remove dirt, grease, oil, mildew, wax and other contaminants. Thoroughly rinse the washed areas and allow to dry completely.

Patch cracks and surface imperfections. Sand repaired areas smooth. When applying over satin, semi-gloss or gloss finishes, sand lightly with medium grit sandpaper for maximum adhesion. Wipe off all sanding dust with a damp cloth. Spot prime patched areas with the appropriate primer or undercoater. Prime unpainted drywall, masonry, and unpainted plaster or wood with Echelon Multi-Purpose Primer. It is essential that plaster be completely dry before priming; allow a minimum of 30 days for new plaster to cure before using Echelon Multi-Purpose Primer.

Prime bare metal with an appropriate metal primer.

Thinning & Clean Up

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean up.

Limitations

Do not apply when air surface or product temperature is below 50° F (10°C) or if temperature might drop to this level within 4 hours of application.

Do not apply in temperatures above 90°F (32°C).

Keep from freezing.

Equipment

Conv. Spray:	Use Sprayer Manufacturers Recommendations
Airless Spray:	Use Sprayer Manufacturers Recommendations
Brush:	Quality nylon / polyester brush
Roller:	3/8" Nap Cover
Pad:	Standard

Packaging

Gallons, Quarts

Colors

White & Tint Bases

Specification Data

Type:	Acrylic Latex
Finish:	Satin
Gloss:	8-12 @ 60°
Sheen:	30-40 @ 85°
% Solids:	
By Weight:	53%
By Volume:	37%
Wt./Gallon:	11.28 ± .10
Flashpoint:	N/A
VOC lbs./gal (max):	1.25
VOC grm/ltr (max):	150
Thinner:	Water
Clean up:	Soap and Water
Dry Time:	
To Touch:	½ hour
To Recoat:	2 - 4 hours
To Service:	Overnight
Thickness:	
Dry:	1.6 mil
Wet:	4.0 mil
Coverage:	400 sq. ft./gal (on smooth surfaces)
Flame Spread Rate:	Class A (0-25 on non-combustible surfaces)